

In the claims:

36. (Currently Amended) Apparatus for facilitating sealing of a puncture formed in a proximal lateral surface of a vessel, the apparatus comprising:

a bar having proximal and distal ends and a first bore extending laterally therethrough; and

a filament disposed through the first bore, wherein the bar is configured to apply ~~[[a]]~~ an internal compressive force upon a distal lateral surface of a vessel such that a lumen of the vessel is narrowed.

37. (Previously Presented) The apparatus of claim 36, further comprising a delivery sheath having proximal and distal ends, a lumen extending therebetween and a sharpened tip at the distal end, wherein the lumen is configured to contain the bar and filament.

38. (Previously Presented) The apparatus of claim 37, further comprising a push rod disposed in the lumen proximal of the bar.

39. (Previously Presented) The apparatus of claim 36, wherein the bar has a shape chosen from the group

consisting of cylindrical shapes, rectangular shapes, and oval shapes.

40. (Previously Presented) The apparatus of claim 36, wherein the bar comprises a biodegradable material.

41. (Currently Amended) The apparatus of claim 36, further comprising a tensioning device configured to hold the filament in a tensioned state.

42. (Previously Presented) The apparatus of claim 41, wherein the tensioning device comprises:

an upright having upper and lower ends;
a plurality of legs attached to the lower end; and
a grip affixed to the upper end.

43. (Previously Presented) The apparatus of claim 42, wherein the grip comprises a V-shaped groove formed in an elastomeric material.

44. (Previously Presented) The apparatus of claim 36, wherein the first bore is disposed in a central region of the bar.

45. (Previously Presented) The apparatus of claim 36, further comprising an eyelet coupled to the bar, wherein the filament is disposed through both the first bore and the eyelet.

46. (Previously Presented) The apparatus of claim 45, wherein the first bore is disposed in a central region of the bar, and the eyelet is coupled to a distal region of the bar.

47. (Currently Amended) The apparatus of claim 45, ~~further comprising an eyelet coupled to the bar,~~ wherein the eyelet is coupled to a central region of the bar, and the first bore is disposed in a distal region of the bar.

48. (Previously Presented) The apparatus of claim 36, further comprising a second bore extending laterally through the bar, wherein the filament is disposed through both the first bore and the second bore.

49. (Previously Presented) The apparatus of claim 48, wherein the first bore is disposed in a central region of the bar, and the second bore is disposed in a distal region of the bar.

50. (Previously Presented) Apparatus for facilitating sealing of a puncture formed in a proximal lateral surface of a vessel, the apparatus comprising:

- a bar having proximal and distal ends and a first eyelet coupled to the bar; and
- a filament disposed through the first eyelet, wherein the bar is configured to apply ~~[[a]]~~ an internal compressive force upon a distal lateral surface of a vessel such that a lumen of the vessel is narrowed.

51. (Previously Presented) The apparatus of claim 50, wherein the first eyelet is coupled to a central region of the bar.

52. (Previously Presented) The apparatus of claim 50, wherein the bar further comprises a second eyelet coupled to the bar, wherein the filament is disposed through the first eyelet and the second eyelet.

53. (Previously Presented) The apparatus of claim 52, wherein the first eyelet is coupled to a central region of the bar, and the second eyelet is coupled to a distal region of the bar.

54. (Previously Presented) The apparatus of claim 50, further comprising a delivery sheath having proximal and distal ends, a lumen extending therebetween and a sharpened tip at the distal end, wherein the lumen is configured to contain the bar and filament.

55. (Previously Presented) The apparatus of claim 54, further comprising a push rod disposed in the lumen of the delivery sheath proximal of the bar.

56. (Previously Presented) The apparatus of claim 50, wherein the bar comprises a biodegradable material.

57. (Previously Presented) The apparatus of claim 50, further comprising a tensioning device configured to hold the filament in a tensioned state so that the vessel is narrowed sufficiently to cause coagulation of blood near the puncture.

58-70. (Withdrawn).

71. (New) The apparatus of claim 36, wherein the internal compressive force is sufficient to cause the vessel to narrow and promote coagulation of blood near the puncture.

72. (New) The apparatus of claim 41, wherein the vessel is narrowed sufficiently to promote coagulation of blood in the vicinity of the puncture.